

CANTILEVERED TARGET TOPPING APPLICATOR, MODEL # QTTC4000

Waterfall Applicator, capable of evenly applying a variety of toppings to your product. Precise electrical controls and changeable hopper widths allow for targeted depositing onto a variety of products. Our cantilevered waterfall topping applicator is a simple, easy to use system.

SPECIFICATIONS

PRODUCT:

Trays, Baked Goods, Pans, etc...

TOPPINGS:

Shredded Cheese

IQF Meats and Vegetables

PRODUCTION RATE:

Up to 75 feet of product per minute.

PORTION:

Application depends on size and consistency of product.

HOPPER:

15 pounds (approx.)

DRIVE SYSTEM:

Rake utilizes precision electric drive motors. Conveyor is Servomotor driven

ELECTRICAL:

240 vac., 3 phase 20 amp circuit 60 Hz. Stainless steel control enclosure.

Frame:

Cantilevered Design Stainless steel construction Polyurethane belting

OPERATOR INTERFACE:

Color Touch Screen HMI

FEATURES:

USDA compliant construction Continuous smooth welds Modular design Mounted on casters Corrosion resistant stainless steel frame

Sanitary design

Easy belt change (no tools required)

Specifications subject to change without notice. Information contained in this document for reference use only.



*QTTC4000 Shown with optional feed conveyor