



CONVEYORIZED TOPPING APPLICATOR, MODEL # TC-3

Waterfall Applicator, capable of evenly applying a variety of toppings to your product. Our conveyORIZED waterfall topping applicator is a simple, easy to use system.

SPECIFICATIONS

PRODUCT:

Rigid or supported products.

TOPPINGS:

Rigid crust or crust supported by corrugated cardboard. bread, pies, cakes, or other rigid products.

PRODUCTION RATE:

Up to 60 feet of product per minute.

PORTION:

Waterfall application depends on size and consistency of product.

HOPPER:

15 pounds (approx.)

DRIVE SYSTEM:

Conveyors and Rake utilize precision electric drive motors.

ELECTRICAL:

240 vac., 1 phase 20 amp circuit 60 Hz.
Stainless steel control enclosure.

CONVEYOR:

Stainless steel construction
Polyurethane belting

OPERATOR INTERFACE:

Color Touch Screen HMI

FEATURES:

USDA compliant construction
Continuous smooth welds
Modular design
Mounted on casters
Consistent product quality
Corrosion resistant stainless steel frame
Sanitary design
Easy belt change



*TC-3 Shown with optional recirculation conveyors

Specifications subject to change without notice. Information contained in this document for reference use only.

QUANTUM TECHNICAL SERVICES, INC.

9524 W GULFSTREAM ROAD FRANKFORT IL 60423 PHONE (888) 464-1540 FAX (815) 464-1541

www.q-t-s.com